



Temperature / Humidity Data Logger

- Models XDL 01+PW/DL+XR 30/70CX
- Models XDL 01+XJDL40D
- The XDL is a temperature and status recording module for refrigerating applications that works in accordance to HACCP rules. It works with Dixell instruments equipped with the serial output or combined with XJDL40D probe module.
- Data can be easily downloaded on a USB key.
- Connection to Dixell controllers that are provided with serial output (through PW-DL)
- Stand-alone operation in a 4 DIN module (XJDL40D provided with 4 NTC probes, 4 DI and 1 relay output).
- Recorded data download on a USB key: txt format that can also be displayed in EXCEL.
- Data recording: up to 1 year with sampling up to 16 minutes (settable).
- TTL and RS485 inputs with internal converter (on PW-DL or XJDL40D).



CAM Regis Multi Probe Data Logger

- Models 15750/52, 15740/42
- Large, high luminosity graphic display
- Setup wizard and text menus in multiple languages, with on-screen help
- 5 channel or 10 channel multi probe data logger
- With or without built-in printer
- Quick print button, to print out the last calendar week of all entries logged
- Internal memory up to three years, with a recording frequency of 15 minutes
- Integrated RS485 communications. ModBus protocol.
- PC based software for monitoring datalogger (optional)
- Application: Industrial and commercial refrigeration, processing industry, healthcare pharmaceutical etc.